Elegance Black FR 6 mm: 10 x 1.50 m (15 m²)

Art. nr - 71676

Scan this QR code to view this product on our website.



Description

Elegance Black FR is an underlay crafted from premium recycled rebond polyurethane foam. This lightweight material ensures a stable and durable installation while enhancing the luxury and comfort of carpets. It's suitable for both residential and commercial use, including entries, restaurants, corridors, rooms, and stairs.

- Excellent resilience
- Lightweight and easy to handle
- Environmentally friendly and 100% recycled
- Fire classification Bfl-s1

Elegance Black FR 6 mm: 10 x 1.50 m (15 m²)

Art. nr - 71676

Specifications

Floor type	Carpet
Thickness	6 mm (10% margin)
Product weight	1360 g/m² (10% margin)
Density	226 kg/m³ (10% margin)
Type of base floor	Wooden floor / Fixed sand cement floor / Floating screed
Domestic use	Yes
Project use	Yes
Wheelchair load (Test method: EN 985)	Suitable, provided double-sided adhesive
Sound-reducing - ΔLw	34 dB ΔLw
TOG rating	2.1 TOG
Thermal resistance - R-value	0.21 m² K/W
Fire classification	Bfl-s1
Flame-retardant - Test method	EN ISO 9239-1
Green choice label	Yes
DIBT certificate	Z-158.10-93
Brand	Best Base
Laying method	Stretching / double-sided adhesive
Product dimensions (Length)	10 m (10% margin)
Product dimensions (Width)	1.5 m
Product dimensions in m2	15 m²

Elegance Black FR 6 mm: 10 x 1.50 m (15 m²)

Art. nr - 71676

Base unit	Roll
Material	Top layer: flame-retardant crêpe / Middle layer: rebond polyurethane foam / Bottom layer: spunbond polypropylene non-woven
Bending strength (Test method: EN 310)	40 N/mm²
Sound-reducing - ΔLw - Test method	ISO 1014-3:2010
Dimensional stability tensile strength / Long / MD	149
Dimensional stability tensile strength / Long / MD - unit	N
Dimensional stability tensile strength / Cross / CD	73
Dimensional stability tensile strength / Cross / CD- unit	N
Dimensional stability tensile strength / Cross / CD - Test method	ISO 13934-1
Dimensional stability elongation / stretch / Long / MD	5

Elegance Black FR 6 mm: 10 x 1.50 m (15 m²)

Art. nr - 71676



















