

Elegance Black FR 6 mm: 10 x 1.50 m (15 m²)

Art. nr - 71676

estillon
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



Description

Elegance Black FR is an underlay crafted from premium recycled rebond polyurethane foam. This lightweight material ensures a stable and durable installation while enhancing the luxury and comfort of carpets. It's suitable for both residential and commercial use, including entries, restaurants, corridors, rooms, and stairs. - Excellent resilience - Lightweight and easy to handle - Environmentally friendly and 100% recycled - Fire retardant Bfl-S1

Elegance Black FR 6 mm: 10 x 1.50 m (15 m²)

Art. nr - 71676

Specifications

Floor type	Carpet
Base unit	Roll
Product weight	1360 g/m ²
Product dimensions (Length)	10 m
Product dimensions in m2	15 m ²
Thickness	6 mm
Density	226 kg/m ³
Material	Top layer: flame-retardant carpet Middle layer: rebond polyurethane foam Bottom layer: spunbond polypropylene non-woven
Brand	Best Base
TOG rating	2.10 TOG
Dimensional stability tensile strength / Long / MD - unit	N
Dimensional stability tensile strength / Cross / CS - unit	N
Dimensional stability elongation / stretch / Long / MD - unit	%
Dimensional stability elongation / stretch / Across / CS - unit	%
Domestic use	Yes
Project use	Yes
Laying method	Stretching / double-sided adhesive

Elegance Black FR 6 mm: 10 x 1.50 m (15 m²)

Art. nr - 71676

Product dimensions (Width)	1.5 m
Product dimensions (Unit)	m ²
Type of base floor	Wooden floor / Fixed sand cement floor / Floating screed
Bending strength (Test method: EN 310)	40 N/mm ²
Wheelchair load (Test method: EN 985)	Suitable, provided double-sided adhesive
Thermal resistance - R-value (Test method: ISO 8302)	0.210 m ² K/W
Sound-reducing L _w (Test method: NEN-EN ISO 717-2)	25 dB L _w
Flame-retardant (Test method: EN 13501-1)	Bfl-S1
Dimensional stability tensile strength / Long / MD; (Test method: DIN EN 10319)	149
Dimensional stability tensile strength / Cross / CD (Test method: DIN EN 10319)	73
Dimensional stability elongation / stretch / Long / MD; (Test method: DIN EN 10319)	5
Dimensional stability elongation / stretch / Across / CD (Test method: DIN EN 10319)	3
Laying direction	Perpendicular to the laying direction of the carpet. Prevent seams of the undercarpet and carpet from coinciding.
Suitable for stair installation	Yes
DIBT certificate	Z-158.10-93
Green Choice	Yes

Elegance Black FR 6 mm: 10 x 1.50 m (15 m²)

Art. nr - 71676

estillon
WE WILL IMPROVE YOUR FLOOR

