

Elegance Green FR 6 mm: 10 x 1,50 m (15 m²)

Art. nr - 716761

estillon
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



Description

Elegance Green FR is a premium carpet underlay based on post-consumer recycled polyurethane foam. Thanks to its higher density, this range offers more support, a firmer and richer feel underfoot, and extra comfort. This makes Elegance Green FR the more luxurious and heavier quality within the range, suitable for domestic and commercial use where comfort and load-bearing performance are key. The range is available in 4, 6 and 7 mm, with a density of 170 to 220 kg/m³ and fire class Bfl-S1.

- Premium quality with higher density
- More support and a fuller feel underfoot
- Extra luxury and comfort under heavier use

Elegance Green FR 6 mm: 10 x 1,50 m (15 m²)

Art. nr - 716761



- Suitable for domestic and commercial use
- Made from post-consumer recycled PU foam
- Available in 4, 6 and 7 mm
- Fire class Bfl-S1

Elegance Green FR 6 mm: 10 x 1,50 m (15 m²)

Art. nr - 716761

estillon
WE WILL IMPROVE YOUR FLOOR

Specifications

Floor type	Carpet
Thickness	6 mm (10% margin)
Product weight	1320 gr/m ² (10% margin)
Density	220 kg/m ³ (10% margin)
Type of base floor	Wooden floor / Fixed sand cement floor / Floating screed
Domestic use	Yes
Project use	Yes
Wheelchair load	Yes
Wheelchair load (Test method: EN 985)	Suitable
Sound-reducing - ΔLw	44 dB ΔLw
TOG rating	1,57 TOG
Thermal resistance - R-value	0,157 m ² K/W
Thermal resistance - Test method	ISO 8302:1991; EN 12667:2001
Flame-retardant	Bfl-s1
Flame-retardant - Test method	EN 13501-1 (2018)
Green choice label	Yes
Brand	Best Base
Stair installation suitable	Yes
Laying method	Stretch fitting / double-sided bonding

Elegance Green FR 6 mm: 10 x 1,50 m (15 m²)




Art. nr - 716761

Product dimensions (Length)	10 m (10% margin)
Product dimensions (Width)	1,5 m
Product dimensions in m ²	15 m ²
Base unit	Roll
Material	Top Layer: Crêpe / Middle Layer: Rebond polyurethane foam - Post Consumer/ Bottom Layer: Spunbond polypropylene non-woven
Installation instruction explanation	Perpendicular to the laying direction of the carpet. Prevent the seams of the underlay and the carpet from coinciding.
Sound-reducing - ΔLw - Test method	ISO 10140-3:2021
Dimensional stability tensile strength / Long / MD	Passed

Elegance Green FR 6 mm: 10 x 1,50 m (15 m²)

Art. nr - 716761

estillon
WE WILL IMPROVE YOUR FLOOR



estillon
GREEN CHOICE

