

# Cloud 9 FR 8 mm: 11 x 1.37 m (15.07 m<sup>2</sup>)

Art. nr - 71691

Scan this QR code to view this product on our website.



## Description

Cloud 9 is an IMO-certified fire-retardant underlay, perfect for ships, offshore installations, hotels, and any location where flame resistance is essential.

# Cloud 9 FR 8 mm: 11 x 1.37 m (15.07 m<sup>2</sup>)

Art. nr - 71691

## Specifications

Floor type	Carpet
Base unit	Roll
Product weight	1334 g/m <sup>2</sup>
Product dimensions (Length)	11 m
Product dimensions in m2	15.07 m <sup>2</sup>
Thickness	8 mm
Density	167 kg/m <sup>3</sup>
Material	Rebond polyurethane foam
Brand	Estillon
TOG rating	1.70 TOG
Domestic use	Yes
Laying method	Stretching / double-sided gluing
Product dimensions (Width)	1.37 m
Product dimensions (Unit)	m <sup>2</sup>
Type of base floor	Wooden floor / Fixed sand cement floor / Floating screed
Wheelchair load (Test method: EN 985)	Suitable
Thermal resistance - R-value (Test method: ISO 8302)	0.170 m <sup>2</sup> K/W
Sound-reducing Lw (Test method: NEN-EN ISO 717-2)	38 dB Lw

# Cloud 9 FR 8 mm: 11 x 1.37 m (15.07 m<sup>2</sup>)

Art. nr - 71691



Laying direction	Perpendicular to the carpet direction. Ensure that the seams of the underlay and carpet do not align.
Suitable for stair installation	Yes
IMO certificate	Yes

# Cloud 9 FR 8 mm: 11 x 1.37 m (15.07 m<sup>2</sup>)

Art. nr - 71691

