

Elegance Green FR 7 mm: 10 x 1,50 m (15 m²)

Art. nr - 717021

estillon
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



Description

Elegance Green FR is a premium carpet underlay made from post-consumer recycled polyurethane foam. Thanks to its higher density, this line offers greater support, a firmer and richer feel underfoot, and extra comfort. This makes Elegance Green FR the more luxurious and heavier quality within the range, suitable for domestic and contract use where comfort and load-bearing performance are more important.

- Premium quality with higher density
- Greater support and a fuller feel underfoot
- Extra luxury and comfort under heavier loads
- Suitable for domestic and contract use
- Made from post-consumer recycled PU foam

Elegance Green FR 7 mm: 10 x 1,50 m (15 m²)

Art. nr - 717021



- Fire classification Bfl-S1

Elegance Green FR 7 mm: 10 x 1,50 m (15 m²)

Art. nr - 717021

estillon
WE WILL IMPROVE YOUR FLOOR

Specifications

Floor type	Carpet
Product weight	1190 gr/m ² (10% margin)
Product dimensions (Length)	10 m (10% margin)
Product dimensions (Width)	1,5 m
Product dimensions in m2	15 m ²
Base unit	Roll
Thickness	7 mm (10% margin)
Density	170 kg/m ³ (10% margin)
Material	Top Layer: Crêpe / Middle Layer: Rebond polyurethane foam / Bottom Layer: Spunbond polypropylene non-woven
Type of substrate	Wooden subfloor / Timber floor Solid cement screed / Fixed sand-cement floor Floating screed
Brand	Best Base
TOG rating	1,83 TOG
Thermal resistance - R-value	0,183 m ² K/W
Thermal resistance - Test method	ISO 8302:1991; EN 12667:2001
Domestic use	Yes
Laying method	Stretch fitting / double-sided bonding
Installation instruction explanation	Perpendicular to the laying direction of the carpet. Prevent the seams of the underlay and the carpet from coinciding
Stair installation suitable	Yes
Green choice label	Yes

Elegance Green FR 7 mm: 10 x 1,50 m (15 m²)

Art. nr - 717021



estillon
WE WILL IMPROVE YOUR FLOOR

Wheelchair load (Test method: EN 985)	Suitable
Sound-reducing - ΔLw	47 dB ΔLw
Sound-reducing - ΔLw - Test method	ISO 10140-3:2021
Flame-retardant	Bfl-s1
Flame-retardant - Test method	EN 13501-1 (2018)
Dimensional stability tensile strength / Long / MD	Passed

Elegance Green FR 7 mm: 10 x 1,50 m (15 m²)

Art. nr - 717021

estillon
WE WILL IMPROVE YOUR FLOOR



estillon
GREEN CHOICE

