

Elegance Green FR 7 mm: 10 x 1,50 m (15 m²)

Art. nr - 717021

estillon
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



Description

Elegance Green FR is a premium underlay based on post-consumer recycled polyurethane foam. Thanks to its higher density, this range offers greater support, a firmer and more luxurious feel underfoot, and extra comfort. This makes Elegance Green FR the more luxurious and heavier-quality option within the range, suitable for domestic and contract use where comfort and load-bearing performance are key. The range is available in 4, 6 and 7 mm, with a density of 170 to 220 kg/m³.

Elegance Green FR 7 mm: 10 x 1,50 m (15 m²)

Art. nr - 717021

estillon
WE WILL IMPROVE YOUR FLOOR

- Premium quality with higher density
- Greater support and a fuller feel underfoot
- Extra luxury and comfort under higher loads
- Suitable for domestic and contract use
- Made from post-consumer recycled PU foam
- Available in 4, 6 and 7 mm

Elegance Green FR 7 mm: 10 x 1,50 m (15 m²)

Art. nr - 717021

estillon
WE WILL IMPROVE YOUR FLOOR

Specifications

Floor type	Carpet
Thickness	7 mm (10% margin)
Product weight	1190 gr/m ² (10% margin)
Density	170 kg/m ³ (10% margin)
Type of base floor	Wooden floor / Fixed sand cement floor / Floating screed
Domestic use	Yes
Project use	Yes
Wheelchair load (Test method: EN 985)	Suitable
Sound-reducing - ΔLw	47 dB ΔLw
TOG rating	1,83 TOG
Thermal resistance - R-value	0,183 m ² K/W
Thermal resistance - Test method	ISO 8302:1991; EN 12667:2001
Flame-retardant - Test method	EN 13501-1 (2018)
Green choice label	Yes
Brand	Best Base
Stair installation suitable	Yes
Laying method	Stretch fitting / double-sided bonding
Product dimensions (Length)	10 m (10% margin)
Product dimensions (Width)	1,5 m

Elegance Green FR 7 mm: 10 x 1,50 m (15 m²)



Art. nr - 717021

Product dimensions in m2	15 m ²
Base unit	Roll
Material	Top Layer: Crêpe / Middle Layer: Rebond polyurethane foam - Post Consumer/ Bottom Layer: Spunbond polypropylene non-woven
Installation instruction explanation	Perpendicular to the laying direction of the carpet. Prevent the seams of the underlay and the carpet from coinciding.
Sound-reducing - ΔLw - Test method	ISO 10140-3:2021
Dimensional stability tensile strength / Long / MD	Passed

Elegance Green FR 7 mm: 10 x 1,50 m (15 m²)

Art. nr - 717021

estillon
WE WILL IMPROVE YOUR FLOOR



estillon
GREEN CHOICE

