

Starbase 4 mm: 10 x 1,50 m (15 m²)

Art. nr - 71820

estillon
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



Description

Starbase is an underlay made from high-quality recycled rebond polyurethane foam. The lightweight foam guarantees a stable and durable installation and enhances the luxury and comfort of the carpet. Starbase is suitable for both residential and commercial applications, such as entrances, restaurants, corridors, rooms, and stairs.

- Exceptional indentation recovery
- Lightweight and easy to handle
- Environmentally friendly and 100% recycled
- Fire retardant Euroclass Bfl-S1

Starbase 4 mm: 10 x 1,50 m (15 m²)

Art. nr - 71820

Specifications

| | |
|---------------------------------------|--|
| Floor type | Carpet |
| Thickness | 4 mm (10% margin) |
| Product weight | 640 g/m ² (10% margin) |
| Density | 160 kg/m ³ (10% margin) |
| Type of base floor | Wooden floor / Fixed sand cement floor / Floating screed |
| Domestic use | Yes |
| Project use | Yes |
| Wheelchair load (Test method: EN 985) | Suitable |
| Sound-reducing - ΔL_w | 25 dB ΔL_w |
| TOG rating | 1.6 TOG |
| Thermal resistance - R-value | 0.16 m ² K/W |
| Flame-retardant | Bfl-S1 |
| Flame-retardant - Test method | EN 13501-1 (2007) + A1 (2013) |
| Green choice label | Yes |
| DIBT certificate | Z-158.10-93 |
| Brand | Best Base |
| Laying method | Stretching / double-sided gluing |
| Product dimensions (Length) | 10 m (10% margin) |
| Product dimensions (Width) | 1.5 m |

Starbase 4 mm: 10 x 1,50 m (15 m²)

Art. nr - 71820




estillon
WE WILL IMPROVE YOUR FLOOR

| | |
|--------------------------|--|
| Product dimensions in m2 | 15 m ² |
| Base unit | Roll |
| Material | Top layer: Crêpe, Middle layer: Rebond polyurethane foam, Bottom layer: Spunbond polypropylene non-woven |

Starbase 4 mm: 10 x 1,50 m (15 m²)

Art. nr - 71820

estillon
WE WILL IMPROVE YOUR FLOOR



Estillon BV
Liesje RI
Starbase®
Verlegbaar te leggen
Breedvoerbaar:
DIN EN 13320-1, E-4
(maximaal estillanbreedte)
Emissiegecertificeerd
volgens de norm
EN15490
Tafelnummer: 2154-10-03

estillon
GREEN CHOICE

