

Starbase 8 mm: 10 x 1,50 m (15 m²)

Art. nr - 71822

estillon
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



Description

Starbase 8 mm: 10 x 1.50 m (15 m²)

Starbase 8 mm: 10 x 1,50 m (15 m²)

Art. nr - 71822

Specifications

| | |
|---------------------------------------|--|
| Floor type | Carpet |
| Thickness | 8 mm (10% margin) |
| Product weight | 1280 g/m ² (10% margin) |
| Density | 160 kg/m ³ (10% margin) |
| Type of base floor | Wooden floor / Fixed sand cement floor / Floating screed |
| Domestic use | Yes |
| Project use | Yes |
| Wheelchair load (Test method: EN 985) | Suitable |
| Sound-reducing - ΔL_w | 29 dB ΔL_w |
| TOG rating | 2.7 TOG |
| Thermal resistance - R-value | 0.27 m ² K/W |
| Flame-retardant | Bfl-S1 |
| Flame-retardant - Test method | EN 13501-1 (2007) + A1 (2013) |
| Green choice label | Yes |
| DIBT certificate | Z-158.10-93 |
| Brand | Best Base |
| Laying method | Stretch / double-sided gluing |
| Product dimensions (Length) | 10 m (10% margin) |
| Product dimensions (Width) | 1.5 m |

Starbase 8 mm: 10 x 1,50 m (15 m²)

Art. nr - 71822





| | |
|--------------------------|--|
| Product dimensions in m2 | 15 m ² |
| Base unit | Roll |
| Material | Top layer: Crêpe Middle layer: Rebond polyurethane foam Bottom layer: Spunbond polypropylene non-woven |

Starbase 8 mm: 10 x 1,50 m (15 m²)

Art. nr - 71822

estillon
WE WILL IMPROVE YOUR FLOOR



Estillon BV
Liesje RL
Starbase®
Verlegwijzer
Bouwen met
DIN EN 13959-1:2018
(normaal ontlaarbaar)
Emissiegecertificeerd
volgens de norm
EN 15647
© 2018
Tafelnummer
7154-10-03

estillon
GREEN CHOICE

