

# Starbase 8 mm: 10 x 1,50 m (15 m<sup>2</sup>)

Art. nr - 71822

**estillon**  
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



## Description

Starbase 8 mm: 10 x 1.50 m (15 m<sup>2</sup>)

# Starbase 8 mm: 10 x 1,50 m (15 m<sup>2</sup>)

Art. nr - 71822

## Specifications

Floor type	Carpet
Thickness	8 mm (10% margin)
Product weight	1280 g/m <sup>2</sup> (10% margin)
Density	160 kg/m <sup>3</sup> (10% margin)
Type of base floor	Wooden floor / Fixed sand cement floor / Floating screed
Domestic use	Yes
Project use	Yes
Wheelchair load (Test method: EN 985)	Suitable
Sound-reducing - $\Delta L_w$	29 dB $\Delta L_w$
TOG rating	2.7 TOG
Thermal resistance - R-value	0.27 m <sup>2</sup> K/W
Flame-retardant	Bfl-S1
Flame-retardant - Test method	EN 13501-1 (2007) + A1 (2013)
Green choice label	Yes
DIBT certificate	Z-158.10-93
Brand	Best Base
Laying method	Stretch / double-sided gluing
Product dimensions (Length)	10 m (10% margin)
Product dimensions (Width)	1.5 m

# Starbase 8 mm: 10 x 1,50 m (15 m<sup>2</sup>)



Art. nr - 71822

Product dimensions in m2	15 m <sup>2</sup>
Base unit	Roll
Material	Top layer: Crêpe Middle layer: Rebond polyurethane foam Bottom layer: Spunbond polypropylene non-woven

# Starbase 8 mm: 10 x 1,50 m (15 m<sup>2</sup>)

Art. nr - 71822

**estillon**  
WE WILL IMPROVE YOUR FLOOR



Estillon BV  
Liesje RL  
Starbase®  
Verlegwijzer  
Bouwerwijzer  
DIN EN 13329-1, 2-4  
(normaal estillamine®)  
Emissiegecertificeerd  
volgens de norm  
EN15247  
© 2018  
Tafelnummer  
7154-10-03

**estillon**  
GREEN CHOICE

