

# Starbase 10 mm: 10 x 1,50 m (15 m<sup>2</sup>)

Art. nr - 71823

**estillon**  
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



## Description

Starbase is an underlay made from high-quality clean recycled rebond polyurethane foam. The lightweight rebond polyurethane foam guarantees a stable, durable installation and enhances the luxurious and comfortable feel of the carpet. Starbase is suitable for residential and commercial applications, such as entrances, restaurants, hallways, and rooms.

- Very high indentation recovery
- Lightweight and easy to work with
- Environmentally friendly production and 100% recycled
- Flame retardant Euroclass Bfl-S1

# Starbase 10 mm: 10 x 1,50 m (15 m<sup>2</sup>)

Art. nr - 71823

## Specifications

Floor type	Carpet
Product weight	1600 g/m <sup>2</sup> (10% margin)
Product dimensions (Length)	10 m (10% margin)
Product dimensions (Width)	1.5 m
Product dimensions in m <sup>2</sup>	15 m <sup>2</sup>
Sound-reducing - ΔL <sub>in</sub> - Test method	ISO 10140-3:2021 / ISO 717-2:2020
Base unit	Roll
Thickness	10 mm (10% margin)
Density	160 kg/m <sup>3</sup> (10% margin)
Material	Top layer: Crêpe Middle layer: Rebond polyurethane foam Bottom layer: Spunbond polypropylene non-woven
Brand	Best Base
TOG rating	3.1 TOG
Thermal resistance - R-value	0.31 m <sup>2</sup> K/W
Domestic use	Yes
Project use	Yes
Laying method	Stretch / double-sided gluing
DIBT certificate	Z-158.10-93
Green choice label	Yes
Type of base floor	Wooden floor / Fixed sand cement floor / Floating screed

# Starbase 10 mm: 10 x 1,50 m (15 m<sup>2</sup>)

Art. nr - 71823

Wheelchair load (Test method: EN 985)	Suitable
Sound-reducing - $\Delta Lw$	48 dB $\Delta Lw$
Sound-reducing - $\Delta Lw$ - Test method	ISO 10140-3:2021 / ISO 717-2:2020
Flame-retardant	Bfl-S1
Flame-retardant - Test method	EN 13501-1 (2007) + A1 (2013)

# Starbase 10 mm: 10 x 1,50 m (15 m<sup>2</sup>)

Art. nr - 71823

**estillon**  
WE WILL IMPROVE YOUR FLOOR

