Felt Underlay $1200 \text{ g/m}^2 - 10 \text{ mm} - 25 \text{ x} 1 \text{ m}$

Art. nr - R912A A1



Scan this QR code to view this product on our website.





Description

Needle felt underlay, easy to cut for durable installation. The underlayment is made from recycled textile fibers. Suitable for residential and construction applications. Good leveling properties High recovery capacity to its original state Enhances the feeling of luxury and comfort Extends the lifespan of the carpet

Felt Underlay $1200 \text{ g/m}^2 - 10 \text{ mm} - 25 \text{ x} 1 \text{ m}$

Art. nr - R912A A1



Specifications

Floor type	Carpet
Base unit	Roll
Product weight	1200 g/m²
Product dimensions (Length)	25 m
Product dimensions (Width)	1 m
Product dimensions in m2	25 m²
Thickness	10 mm
Density	120 kg/m ³
Material	Recycled needle felt
Brand	Roberts
TOG rating	5.09 TOG
Thermal resistance - R-value (Test method: ISO 8302)	0.509 m² K/W
Laying method	Stretching
Product dimensions (Unit)	m²
Type of base floor	Wooden floor / Fixed sand cement floor / Floating screed
Laying direction	Perpendicular to the direction of the carpet. Prevent the seams of the underlay and the carpet from overlapping.
Green Choice	Yes

Felt Underlay $1200 \text{ g/m}^2 - 10 \text{ mm} - 25 \text{ x} 1 \text{ m}$

Art. nr - R912A A1



