

Underlay Technical Specification


Item Code: TALVTLOWGRAB

Issue Date: 22/03/2019

Issue No. 1

Sponge Rubber

Suitable for the installation of luxury vinyl tile flooring




Standard Specifications*

Thickness	1.50 mm	DIN EN 823
Nominal square weight	1500 g/m ²	
Nominal roll weight	15.00kg	
Nominal roll area	10.00 m ² (10.00m x 1.00m)	DIN EIN 822
Reflected Walking Sound†	up to 6%	Tested by manufacturer (form EPLF WD 021029-5) Measured under standard LVT
Impact Sound†	up to 17dB	EPLF Norm 10140 Measured under standard LVT
Thermal Resistance	0.1 togs	BS 4745
Thermal Resistance	0.01m ² K/W	EN 12664 (suitable for water underfloor heating)
Residual Indentation	less than 0.1 mm	DIN EN 3385
Compressive Strength	up to 42 t/m ² (~ 420 kPa)	acc. to DIN EN 826 (250 Pa, 0.5 mm)
Compressive Creep	~ 76 kPa	acc. to DIN EN1606
Dynamic Load	> 100,000 cycles	acc. to DIN EN 13793
Resistance to large ball	650 mm	acc. to EN 13329
Punctual Conformability	0.62 mm	Fpr CEN TS 16354
Flammability Classification	Bfl-s1	DIN EN 1350-1 (excluding covering)

Other Specifications

Odour	No objectionable odour
Antimicrobial and mildew resistant	Yes
Colour	Blue
Packaging	Clear, with printed insert

Certification



Guarantee

Guaranteed for the serviceable lifetime of the flooring.

Notes

* The nominal roll dimensions have been quoted. These may vary slightly but will comply with the requirements of BS EN 14499:2015