

UAK93 RUG ANTI-KREEP

Product Technical Specification

Item Code: TXUAK93

Issue Date: 11/07/2019

Issue No. 1



Polyester fleece

Rug anti-slip mat for use with all floor types

Wood | Stone floor Parquet | PVC, Cork | Ceramics | Laminate |

Standard Specifications*

Nominal square weight	240 g/m ²
Nominal area	25.00m ² (25m x 1m)
Nominal thickness	2.5mm


Other Specifications

Colour	Black/grey
Coating	Acrylic based adhesive
Packaging	Clear film with printed insert

Instructions



Black side up for rugs on carpet



Grey side up for rugs on hard flooring

Properties

- Two sides with different coatings
- Prevents movement or 'walking' of rugs
- Leaves no residue
- Free of plasticizers
- Suitable for use with under-floor heating
- Easy to cut
- Great treadability
- Protects the carpet
- Hand washable at 30°C

Installation

UAK93 RUG ANTI-KREEP® is a multi-purpose non-skid underlay pad. It can be used on wall-to-wall carpeting or on smooth flooring surfaces. In order to obtain maximum satisfaction and the best results with UAK93 RUG ANTI-KREEP®, here are the installation procedures to be followed:

RUG on wall-to-wall carpeting:

- Cut UAK93 RUG ANTI-KREEP® about 1"-3" smaller than the rug to be installed
- Remove the plastic release liner
- Place UAK93 RUG ANTI-KREEP®'s gray side down, facing the smooth floor
- Then place the rug on top of UAK93 RUG ANTI-KREEP®'s Black side.

RUG on smooth flooring surface:

- Cut UAK93 RUG ANTI-KREEP® about 1"-3" smaller than the rug to be installed
- Remove the plastic release liner
- Place UAK93 RUG ANTI-KREEP®'s black side down, facing the wall-to-wall carpeting
- Then place the rug on top of UAK93 RUG ANTI-KREEP®'s gray side.

CUTTING:

UAK93 RUG ANTI-KREEP® can be easily cut with scissors or a utility knife.

FLOOR PREPARATION:

Prior to installing UAK93 RUG ANTI-KREEP®, the floor should be vacuumed, clean and dry. Do not install UAK93 RUG ANTI-KREEP® on a wet floor. In order to obtain a long-lasting non-skid performance, avoid frequent removal and re-installation of UAK93 RUG ANTI-KREEP® from its designated installation area.

OVERSIZED RUGS:

If several pieces of UAK93 RUG ANTI-KREEP® are necessary for one rug, simply apply as many pieces as needed, side-by-side. Taping or splicing is NOT necessary.

Notes

* The nominal roll dimensions have been quoted. These may vary slightly but will comply with the requirements of BS EN 14499:2015

‡ Value derived from similar product test results