

estillon
WE WILL IMPROVE YOUR FLOOR

ELEGANCE BLACK FR / RED

CARPET UNDERLAYS

Elegance Black FR and Elegance Red are underlays made of high quality recycled rebond polyurethane foam. The light weight rebond polyurethane foam guarantees a stable, durable installation and increases the experience of luxury and comfort of carpet.

Elegance Black FR is suitable for domestic and project use, such as the entrance, restaurants, corridors, rooms and stairs.

Elegance Red is suitable for domestic use, such as living room, bedroom, hallway and stairs if glued on both sides.



Elegance Black FR
4 mm - 6 mm



Elegance Red
7 mm

- Excellent compression recovery capability
- Lightweight and easy to install
- Environmental friendly produced and 100% recycled material
- Fire retardant Euroclass Bfl-S1 (**Elegance Black**)

ELEGANCE BLACK FR / RED

CARPET UNDERLAYS

Specifications Elegance Black FR/Red

	Elegance Black FR 4 mm	Elegance Black FR 6 mm	Elegance Red 7 mm
Thickness	4 mm	6 mm	7 mm
Dimensions	10 m x 1,5 m = ± 15 m ²	10 m x 1,5 m = ± 15 m ²	10 m x 1,5 m = ± 15 m ²
Weight	960 gr / m ²	1360 gr / m ²	1120 gr / m ²
Density	220 kg / m ³	220 kg / m ³	170 kg / m ³
Material	High quality recycled rebond polyurethane foam	High quality recycled rebond polyurethane foam	High quality recycled rebond polyurethane foam
Stability traction	40 N / mm ² / length 149 N / width 73 N	40 N / mm ² / length 149 N / width 73 N	40 N / mm ² / length 156 N / width 62 N
Stability extension	10 % / length 5 % / width 3 %	10 % / length 5 % / width 3 %	10 % / length 5 % / width 3 %
Wheelchair test	Suitable, double stick only	Suitable, double stick only	Suitable, double stick only
Impact sound reduction	ΔLw = 25 dB	ΔLw = 36 dB	ΔLw = 26 dB
Thermal resistance	0,16 m ² K / W	0,21 m ² K / W	0,20 m ² K / W
Fire retardency	Bfl-S1	Bfl-S1	Efl-S1
ASTM radial panel test	Class I	Class I	NA
Russian requirements on fire safety	Class KM3	Class KM3	Class KM3