



estillon
WE WILL IMPROVE YOUR FLOOR




XPS

THE IDEAL UNDERLAY TO USE WITH LAMINATE AND LVT CLICK FLOORS

XPS LVT 1,5 mm is a high density XPS foam underlay with a anti slip layer, has a high compressive strength and creates a fully flat and smooth basis for your LVT click and laminate floors. XPS LVT 1,5 mm is suitable for domestic and commercial use.

XPS 2.2 is a high density XPS foam underlay with a moisture barrier. XPS 2.2 has a high compressive strength and creates a fully flat and smooth basis for your laminate floors. Suitable for laminate floorings for domestic and commercial use.



**XPS LVT
1.5mm**



**XPS Laminate
2.2mm**

- Material xps foam
- High Compressions strength
- Creates a fully flat and smooth basis
- High level of load resistance
- Suitable for domestic use and commercial



estillon
WE WILL IMPROVE YOUR FLOOR

XPS

Specifications XPS range

	XPS LVT 1,5 mm	XPS Laminate 2,2 mm
Thickness	1.5 mm	2.2 mm
Dimensions	8.5x1.18 m = +/-10.03 m ²	5.1x1.18 m = +/-6.018 m ²
Weight	150 gr/m ²	70 gr/m ²
Density	100 kg/m ³	32 kg/m ³
Material	AS Layer/High density XPS foam	Moisture barrier/High density XPS foam
Punctual conformity	0.2 mm	0.2 mm
High compression strength	Class CS3 - CS > 400kPa	Class CS1 - CS > 90kPa
Weelchair test	Passed	Passed
Impact sound reduction	$\Delta L_w=21$ dB	$\Delta L_w=19$ dB
Fire retardency	Efl-S1	Efl-S1

MORE INFORMATION AT WWW.ESTILLON.COM